

# Safety Data Sheet according to 91/155/EEC

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

## ACETONE

00642-0003

### 1. Identification of the substance/preparation and of the company/undertaking

#### 1.1 Identification of the substance or preparation

ACETONE

#### **Use of the substance/preparation**

Cosmetic

#### 1.2 Company/undertaking identification

European Nail Factory

In der Salzheck 7

D-56332 Dieblich

Telephone : ++49 (0) 26 07-96 60-0

Telefax : ++49 (0) 26 07-96 60-29

Contact person :

Internet: [www.europeannailfactory.com](http://www.europeannailfactory.com)

Inquiry office :

Emergency telephone : ++49 (0) 2607 / 96600 European Nail Factory GmbH, available during open hours

---

### 2. Composition/information on ingredients

Chemical characterization ( substance )

#### **Hazardous components**

EC-No.	CAS-No.	Chemical name	Quantity	Classification
200-662-2	67-64-1	acetone, propan-2-one, propanone	50 - 100 %	F, Xi R11-36-66-67

Full text of each relevant R phrase can be found in heading 16.

---

### 3. Hazards identification

#### **Classification**

Symbols : Highly flammable, Irritant

R-phrases :

Highly flammable.

Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

---

### 4. First aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

#### **After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.

If patient is not breathing, apply artificial respiration.

#### **After contact with skin**

Wash off with soap and plenty of water.

Do not use solvents or thinners.

Consult a doctor if skin irritation persists.

**Safety Data Sheet according to 91/155/EEC**

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

**ACETONE**

00642-0003

---

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.  
Immediately give plenty of water (if possible charcoal slurry).  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

**Advice to doctor**

Attention. Beware, danger of aspiration.  
Risk of pulmonary oedema.

---

**5. Fire-fighting measures**

**Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

**Extinguishing media which must not be used for safety reasons**

Full water jet

**Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases**

Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>).

**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.  
Protective suit

**Additional information**

Backfire at a long distance is possible.  
Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**6. Accidental release measures**

**Personal precautions**

In case of vapour formation use respirator.  
Do not smoke.  
Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.  
Do not discharge into the subsoil/soil.

**Methods for cleaning up/taking up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Take up mechanically and collect in suitable container for disposal.

**Additional information**

Clean contaminated surface thoroughly.

## Safety Data Sheet according to 91/155/EEC

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

### ACETONE

00642-0003

---

## 7. Handling and storage

### 7.1 Handling

#### Advice on safe handling

Keep container tightly closed.

Do not breathe vapours.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take measures against electrostatically charging.

Use only explosion-proof equipment.

### 7.2 Storage

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Protect against direct sun radiation.

Keep at temperatures between 5°C and 40°C.

#### Advice on storage compatibility

Incompatible with:

Oxidizing agents, Acids and bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI) : 3 A

---

## 8. Exposure controls/personal protection

### 8.1 Exposure limit values

#### Exposure limits (EH40)

CAS No.	Substance	ml/m <sup>3</sup>	mg/m <sup>3</sup>	F/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
	Acetone	1500	3620		STEL (15 min)	WEL

### 8.2 Exposure controls

#### Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Take off immediately all contaminated clothing.

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

#### Hand protection

## Safety Data Sheet according to 91/155/EEC

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

### ACETONE

00642-0003

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Eye protection

Eye wash bottle with pure water.

Tightly fitting goggles

#### Skin protection

Long sleeved clothing.

---

## 9. Physical and chemical properties

### 9.1 General information

Physical state : Liquid  
Colour : Colourless  
Odour : Like acetone

### 9.2 Important health, safety and environmental information

		Test method
<b>Changes in the physical state</b>		
Boiling point :	56 °C	
Flash point :	- 20 °C	DIN 53213
<b>Flammability</b>		
Lower explosion limits :	2,6 vol. %	
Upper explosion limits :	13,0 vol. %	
Ignition temperature :	465 °C	
Vapour pressure :	247 hPa	
at (20 °C)		
Density (at 20 °C) :	0,79 g/cm <sup>3</sup>	DIN 53217
Water solubility :	Completely miscible	
at (20 °C)		
Flow time :	11 s	4 DIN 53211
at (23 °C)		
<b>Solvent content</b>		
100 %		

---

## 10. Stability and reactivity

### Conditions to avoid

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

### Materials to avoid

Oxidizing agents., Acids and bases

### Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

### Additional information

No decomposition if stored and applied as directed.

## Safety Data Sheet according to 91/155/EEC

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

**ACETONE**

00642-0003

---

### 11. Toxicological information

#### **Empirical data on effects on humans**

Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness or cracking.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Concentration above the admissible concentration at the workplace may cause dizziness, headache and inebriation.

Attention. Beware, danger of aspiration.

---

### 12. Ecological information

#### **Additional information**

Do not flush into surface water or sanitary sewer system.

Slightly water hazardous.

---

### 13. Disposal considerations

#### **Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

#### **Waste disposal number of waste from residues/unused products :**

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors

Classified as hazardous waste.

#### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

---

### 14. Transport information

#### **Land transport (ADR/RID)**

ADR/RID class :	3
Hazard-no. :	33
UN number :	1090
Hazard label :	3
ADR/RID packing group :	II

#### **Description of the goods**

Acetone

#### **Remarks (land transport)**

LQ 4: combination packaging: 3 I / 30 kg (total gross mass); trays: 1 I / 20 kg (total gross mass).

#### **Inland waterways transport**

#### **Marine transport**

## Safety Data Sheet according to 91/155/EEC

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

### ACETONE

00642-0003

---

IMDG code :	3
UN number :	1090
Marine pollutant :	No
EmS :	F-E, S-D
IMDG packing group :	II
Hazard label :	3

#### Description of the goods

ACETONE

#### Remarks (marine transport)

Limited quantities (section 3.4): combination packaging: 5 l / 30 kg (total gross mass); trays: 5 l / 20 kg (total gross mass).

#### Air transport

ICAO/IATA-DGR :	3	
UN/ID number :	1090	
Hazard label :	3	
IATA-packing instructions - Passenger :		305
IATA-max. quantity - Passenger :		5 L
IATA-packing instructions - Cargo :		307
IATA-max. quantity - Cargo :		60 L
ICAO packing group :	II	

#### Description of the goods

ACETONE

---

## 15. Regulatory information

### 15.1 Labelling

Indication of danger : F - Highly flammable; Xi - Irritant

Labelling according to EC-guidelines : According to the EC hazardous substance regulations in compliance with the EC cosmetic product regulations this product must not be labelled as a hazardous substance.

According to ruling EC Directives the product must be labelled as hazardous substance as follows:

#### R phrases :

11	Highly flammable.
36	Irritating to eyes.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

#### S phrases :

09	Keep container in a well-ventilated place.
16	Keep away from sources of ignition - No smoking.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
35	This material and its container must be disposed of in a safe way.

### 15.2 National regulations

Employment restrictions : Observe employment restrictions for young people.; Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class : 1 - slightly water contaminating

1999/13/EC (VOC) : 100 %

**Safety Data Sheet according to 91/155/EEC**

European Nail Factory

Revision date : 16.12.2005

Revision no. : 1,00

**ACETONE**

00642-0003

---

**16. Other information**

**List of relevant R phrases**

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

**Other data**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"